

sewoo

3-Inch Direct Thermal POS Printer

SLK-TL100II




- Fast printing speed(200mm/sec)
- Maximize productivity with Compact and Sleek design
- The simplest and efficient design for environments with limited space
- Reduce power consumption and cost through energy star certification
- High reliability mechanism: 1.5 Million of Cutter life and 160km of TPH Life



Barcode



Durable



Paper
Width




Light
Weight



Easy
Loading



Fast Speed



Compact
Design



Easy
Maintenance

APPLICATION

SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method
Direct thermal

Print Speed
Up to 200mm/sec(7.8ips)

Print Width
Up to 72mm(2.8")

Resolution
180 dpi

Power
Power type : External SMPS
AC : 100~240Vac 50/60Hz
DC : 24Vdc / 1.75A

Sensor
Standard: Paper end, Paper low ,
Cover open
Optional: Black mark

Reliability
TPH life : 160km
MCBF : 60 Million lines
Cutter life : 2.0 Million cuts

Drawer port
2 Circuit(24V, 1A Max.)



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)
136 x 165 x 111mm
(5.35" x 6.49" x 4.37")
Weight
1.0Kg(2.2lb)



INTERFACES

Standard
USB(B type)+Serial(RS-232C_9pin)
Built-in
Optional
Bluetooth Smart Ready
(Bluetooth5.2+BLE)



CERTIFICATIONS

KC, CE, FCC, IC, CB, NRTL



OPERATING CHARACTERISTICS

Operating Temperature
41 ~ 104°F(5 ~ 40°C)
Operating Humidity
10 ~ 90%
Storage Temperature
-4 ~ 140°F(-20 ~ 60°C)
Storage Humidity
10 ~ 90%



MEDIA CHARACTERISTICS

Media Type
Thermal receipt paper
Media Width
79mm ± 0.5mm
Media Core Diameter
12.5mm ± 0.5mm
Media Roll Diameter
Max. ø 83mm
Thickness
0.06~0.09mm



SOFTWARE

Emulations
ESC/POS Command compatible
Drivers
Windows Driver(XP ~, Server2003 ~),
Windows CE & Mobile Driver (CE 4.2 ~,
Mobile 5.0 ~), Linux Driver, Mac Driver,
OPOS Driver, JavaPOS Driver, iOS SDK,
Android(6.0 ~) SDK, Windows SDK,
Windows CE SDK, Linux SDK



BARCODES

1D
EAN-8, EAN-13, Code 39, Code 93,
Code 128, ITF, UPC-A, UPC-E, Codabar
2D
PDF 417, QR code, DATA MATRIX



FONTS / GRAPHICS

Character Type
Font A(12x24), Font B(9x17),
Chinese(Traditional/Simplified, 24x24),
Korean(24x24), Japanese(24x24)
Characters per line (CPL)
Font A(12x24) : 42cpl,
Font B(9x17) : 56cpl,
Chinese/Korean/Japanese: 21cpl
Character set
95 Alphanumeric,
14 International,
128 x 18 Graphic



ACCESSORIES

Standard
Power Adaptor 24Vdc / 1.75A
Optional
Melody box, 24V Buzzer,
Paper Guide

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea
T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA
T. +1-310-617-7401
E. NA_Sales@miniprnter.com

México

Cauahuéemoc, Mexico D.F.
T. +52-1-55-143893 M. +52-1-55-3232-9543
E. LA_Sales@miniprnter.com

