

sewoo

DIRECT THERMAL POS PRINTER

SLK-TE322II_L



- Various O/S drivers : Windows Driver (XP ~,Server2003 ~), Windows CE & Mobile Driver (CE 4.2 ~,Mobile 5.0 ~), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver, iOS SDK, Android(6.0 ~) SDK, Windows SDK, Windows CE SDK, Linux SDK
- Energy star qualified for power efficiency
- Paper width adjustable 50~82.5mm
- ESC/POS command compatible
- Support restick printing



Barcode



Durable

50~82.5MM

Paper width



Paper Sensor



Energy Star



Easy Loading



Fast Speed



Compact Design



Easy Maintenance



Various interface



Restick

APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method

Direct thermal

Print Speed

Max. 220mm/sec

Restick : Max. 160mm/sec(6.2ips)

Print Width

Max. 72mm(2.8")

Resolution

180dpi/203dpi

Power

Power type : External SMPS

AC : 100~240Vac 50/60Hz

DC : 24Vdc / 1.75A

Sensor

Standard: Paper End, Paper Low,

Cover Open

Option : Black Mark

Reliability

TPH life : 160km

Restick TPH life : 100km

MCBF : 60 Million lines

Cutter life : 1.5 Million cuts

Restick cutter life : 1 Million cuts

Drawer port

2 circuits(24V, 1A Max.)



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)

156 x 206 x 155mm

(6.14" x 8.11" x 6.10")

Weight

1.7Kg(3.74lb)



INTERFACES

Standard

USB(B type)

Option

Serial(RS-232C), Parallel(IEEE1284),

Ethernet, Wi-Fi(802.11 a/b/g/n),

Bluetooth Ver2.1(Movon,iOS)

Bluetooth Smart Ready

(Bluetooth5.2+BLE)



CERTIFICATIONS

CE, FCC, KC, UL/cUL,

ENERGY STAR



OPERATING CHARACTERISTICS

Operating Temperature

0 ~ 45°C(32 ~ 113°F)

Restick : 0 ~ 30°C(32 ~ 86°F)

Operating Humidity

35 ~ 80%

Storage Temperature

-20 ~ 60°C(-4 ~ 140°F)

Storage Humidity

10 ~ 90%



MEDIA CHARACTERISTICS

Media Type

Thermal receipt paper

Restick(Optional)

Media Width

50mm ~82.5mm(1.9~3.2")

Media Core Diameter

12.5mm ± 0.5mm(0.4")

Media Roll Diameter

ø 80mm(3.1")

Thickness

0.06~0.09mm



SOFTWARE

Emulations

ESC/POS Command compatible

Drivers

Windows Driver(XP ~, Server2003 ~),

Windows CE & Mobile Driver (CE 4.2 ~,

Mobile 5.0 ~), Linux Driver, Mac Driver,

OPOS Driver, JavaPOS Driver, iOS SDK,

Android(6.0 ~) SDK, Windows SDK,

Windows CE SDK, Linux SDK



BARCODES

1D

EAN-8, EAN-13, Code 39,

Code 93, Code 128, ITF,

UPC-A, UPC-E, Codabar

2D

PDF 417, QR code, DATA MATRIX



FONTS / GRAPHICS

Character Type

Font A(12x24), Font B(9x17),

Chinese(Traditional/Simplified, 24x24),

Korean(24x24), Japanese(24x24)

Characters per line (CPL)

Font A(12x24) : 42cpl,

Font B(9x17) : 56cpl,

Character set

95 Alphanumeric,

14 International,

128 x 18 Graphic



ACCESSORIES

Standard

Power Adaptor 24Vdc / 1.75A

Option

Melody Box

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA

T. +1-859-992-5936

E. NA_Sales@miniprnter.com

México

Cuauhtémoc, Mexico D.F.

T. +52-1-55-143893

M. +52-1-55-3232-9543

E. LA_Sales@miniprnter.com

