

sewoo

Compact size and Enhanced usability

# SLK-TS400EB




- Structure for easy maintenance
- Design for enhanced usability
- Compact footprint to help easily fit on the counter.
- Ideal for front exit printing with Wall mount.
- Supports flexible printing exit way Front exit or top exit.
- Ideal for kitchen/bar printer with melody box(Kitchen buzzer)
- Easy handling the jam of the paper with same cover opening/closing direction as paper cutting direction.



Barcode



Durable



Paper  
Width



Easy  
Loading



High  
Speed



Compact  
Design



Easy  
Maintenance



Various  
interface

## APPLICATION



## SPECIFICATIONS

### PRINTER CHARACTERISTICS

**Print Method**  
Direct thermal

**Print Speed**  
Up to 220mm/sec(8.6ips)

**Print Width**  
Up to 72mm

**Resolution**  
180 dpi

**Power**  
Power type : External SMPS  
AC : 100~240Vac 50/60Hz  
DC : 24Vdc / 1.75A

**Sensor**  
Paper end, Cover open

**Reliability**  
TPH life : 160km  
MCBF : 60 Million lines  
Cutter life : 2.0 Million cuts

**Drawer port**  
2 circuits(24V, 1A Max.)

### PHYSICAL CHARACTERISTICS

**Dimension (W x D x H)**  
130×140×154mm  
(5.11"×5.51"×6.06")

**Weight**  
1.25Kg(2.7lb)

### INTERFACES

**Standard**  
USB(B type)+Ethernet Built-in

**Optional**  
Bluetooth Smart Ready  
(Bluetooth4.2+BLE)  
or WiFi(802.11a/b/g/n)

### CERTIFICATIONS

CE, FCC, KC, UL/cUL, CB,  
ENERGY STAR, TELECr

### OPERATING CHARACTERISTICS

**Operating Temperature**  
32 ~ 113°F(0 ~ 45°C)

**Operating Humidity**  
35 ~ 80%

**Storage Temperature**  
-4 ~ 140°F(-20 ~ 60°C)

**Storage Humidity**  
10 ~ 90%

### MEDIA CHARACTERISTICS

**Media Type**  
Thermal receipt paper

**Media Width**  
80mm(3.14")

**Media Core Diameter**  
12.5mm ± 0.5mm (0.4")

**Media Roll Diameter**  
Max. ø 83mm

**Thickness**  
0.05~0.09mm

### SOFTWARE

**Emulations**  
ESC/POS Command compatible

**Drivers**  
Windows Driver(XP ~, Server2003 ~),  
Windows CE & Mobile Driver (CE 4.2 ~,  
Mobile 5.0 ~), Linux Driver, Mac Driver,  
OPOS Driver, JavaPOS Driver, iOS SDK,  
Android(6.0 ~) SDK, Windows SDK,  
Windows CE SDK, Linux SDK

### BARCODES

**1D**  
EAN-8, EAN-13, Code 39, Code 93,  
Code 128, ITF, UPC-A, UPC-E, Codabar

**2D**  
PDF 417, QR code, DATA MATRIX

### CHARACTERS / GRAPHICS

**Character Type**  
Font A(12x24), Font B(9x17),  
Chinese(Traditional/Simplified, 24x24),  
Korean(24x24), Japanese(24x24)

**Characters per line (CPL)**  
Font A(12x24) : 42cpl,  
Font B(9x17) : 56cpl,

**Character set**  
95 Alphanumeric,  
14 International,  
128 x 18 Graphic

### ACCESSORIES

**Standard**  
Power Adaptor 24Vdc / 1.75A

**Optional**  
Melody box, 24V Buzzer

# sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea  
T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA  
T. +1-310-617-7401  
E. NA\_Sales@miniprnter.com

México

Cuauhtémoc, Mexico D.F.  
T. +52-1-55-143893 M. +52-1-55-3232-9543  
E. LA\_Sales@miniprnter.com

