

# sewoo

## 3-Inch POS Printer

# SLK-TS200



- Simple and sleek design
- High Performance Easy Maintenance
- Wheel-type paper jam control
- High speed printing at 250mm/sec(9.8ips)
- Visible wireless connectivity status
- Ideal for top exit printing with wall mount
- Simple and easy replacement of components including head, motor, cutter, PCB, etc



WiFi




Bluetooth



Barcode



Durable




Paper Width



Easy Loading



Fast Speed



Compact Design



Easy Maintenance

## APPLICATION



## SPECIFICATIONS

### **PRINTER CHARACTERISTICS**

#### Print Method

Direct thermal

#### Print Speed

Up to 250mm/sec(9.8ips)

#### Print Width

Up to 72mm(2.8")

#### Resolution

203dpi

#### Power

Power type : External SMPS

AC : 110~220Vac 50/60Hz

DC : 24Vdc / 2.5A

#### Sensor

Paper end, Cover open

#### Reliability

TPH life : 150km

MCBF : 80 Million lines

Cutter life : 2.0 Million cuts

Cutter method: Partial / Full cut  
(Command or tool setting)

#### Speaker

3type built in melody

#### Drawer port

1 circuit(24V, Max. 1A)

### **PHYSICAL CHARACTERISTICS**

#### Dimension (W x D x H)

174×136×132mm

(6.85"×5.35"×5.19")

#### Weight

1.04Kg(2.3lb)

### **INTERFACES**

#### Standard

USB(B type)+Serial

(RS- 232C\_9pin)+Ethernet Built-in

#### Optional

Bluetooth Smart Ready

(Bluetooth5.0+BLE)

or WiFi(802.11a/b/g/n)

### **CERTIFICATIONS**

KC, CE, FCC, IC, CB,

cTUVus, Energy Star

### **OPERATING CHARACTERISTICS**

#### Operating Temperature

32 ~ 113°F(0 ~ 45°C)

#### Operating Humidity

10 ~ 80%

#### Storage Temperature

4 ~ 140°F(-10 ~ 60°C)

#### Storage Humidity

10 ~ 90%

### **MEDIA CHARACTERISTICS**

#### Media Type

Thermal receipt paper

Black mark paper

#### Media Width

Max.58mm/80mm

#### Media Core Diameter

12.5mm ± 0.5mm

#### Media Roll Diameter

Max. ø 83mm

#### Thickness

0.05~0.08mm

### **SOFTWARE**

#### Emulations

ESC/POS Command compatible

#### Drivers

Windows Driver(XP ~, Server2003 ~),

Linux Driver, Mac Driver, OPOS Driver,

JavaPOS Driver

#### SDK

Android SDK, iOS SDK, Windows SDK

### **BARCODES**

#### 1D

EAN-8, EAN-13, Code 39, Code 93,

Code 128, ITF, UPC-A, UPC-E, Codabar

#### 2D

PDF 417, QR code

### **FONTS / GRAPHICS**

#### Character Type

Font A(12x24), Font B(9x17),

Chinese(Traditional/Simplified, 24x24),

Korean(24x24), Japanese(24x24)

#### Characters per line (CPL)

· 180dpi

Font A(12x24) : 42/30cpl

Font B(9x17) : 59/40cpl

· 203dpi

Font A(12x24) : 48/35cpl

Font B(9x17) : 64/46cpl

#### Character set

95 Alphanumeric,

16 International,

128 x 18 Graphic

### **ACCESSORIES**

#### Optional

Melody box, 24V Buzzer,

2inch Paper Guide

#### Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

#### USA, Inc.

Torrance, CA 90502, USA

T. +1-859-992-5936

E. NA\_Sales@miniprnter.com

#### México

Cuauhtémoc, Mexico D.F.

T. +52-1-55-143893

M. +52-1-55-3232-9543

E. LA\_Sales@miniprnter.com

