

sewoo

DIRECT THERMAL POS PRINTER

SLK-T12EB_L



- Energy star qualified for power efficiency
- High speed printing : 220mm/sec
- Paper width adjustable 50~82.5mm
- ESC/POS command compatible
- 2D barcode supported
- Easy troubleshooting of paper jam by separating cutter cover
- Support restick printing



Barcode



Durable



Paper Width



Paper Sensor



Various interface



Easy Loading



Fast Speed



Compact Design



Easy Maintenance



Energy Star



Restick

APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method

Direct thermal

Print Speed

Max. 220mm/sec

Restick : Max. 160mm/sec

Print Width

Max. 72mm

Resolution

Standard: 180dpi

Restick : 203dpi

Power

Power type : External SMPS

AC : 100~240Vac 50/60Hz

DC : 24Vdc / 1.75A

Sensor

Standard: Paper End, Paper Low,

Cover Open

Option : Black Mark

Reliability

TPH life : 160km

Restick TPH life : 100km

MCBF : 60 Million lines

Cutter life : 1.8 Million cuts

Restick cutter life : 1 Million cuts

Drawer port

2 circuits(24V, 1A Max.)



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)

152 x 202 x 150.5mm

Weight

1.7Kg



INTERFACES

Standard

USB(B type)+Serial(RS-232C_9pin)

+Ethernet Built-in



CERTIFICATIONS

CE, FCC, KC, UL/cUL,

ENERGY STAR



OPERATING CHARACTERISTICS

Operating Temperature

0 ~ 45°C

Restick : 0 ~ 30°C

Operating Humidity

35 ~ 80%

Storage Temperature

-20 ~ 60°C

Storage Humidity

10 ~ 90%



MEDIA CHARACTERISTICS

Media Type

Thermal receipt paper,

Restick(Optional)

Media Width

50mm ~82.5mm

Media Core Diameter

12.5mm ± 0.5mm

Media Roll Diameter

ø 80mm

Thickness

0.05~0.09mm



SOFTWARE

Emulations

ESC/POS Command compatible

Drivers

Windows Driver(XP ~, Server2003 ~),

Windows CE & Mobile Driver (CE 4.2 ~,

Mobile 5.0 ~), Linux Driver, Mac Driver,

OPOS Driver, JavaPOS Driver,

SDK

iOS SDK, Android(6.0 ~) SDK,

Windows SDK, Windows CE SDK, Linux SDK



FONTS / GRAPHICS

Character Type

Font A(12x24), Font B(9x17),

Chinese(Traditional/Simplified, 24x24),

Korean(24x24), Japanese(24x24)

Characters per line (CPL)

Font A(12x24) : 42cpl

Font B(9x17) : 56cpl

Character set

95 Alphanumeric

14 International

128 x 18 Graphic



BARCODES

1D

EAN-8, EAN-13, Code 39,

Code 93, Code 128, ITF,

UPC-A, UPC-E, Codabar

2D

PDF 417, QR code, DATA MATRIX



ACCESSORIES

Standard

Power Adaptor 24Vdc / 1.75A

Option

Melody Box



COLOR

Cool grey, Ivory

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprinter.com

www.miniprinter.com

USA, Inc.

Torrance, CA 90502, USA

T. +1-859-992-5936

E. NA_Sales@miniprinter.com

México

Cuauhtémoc, Mexico D.F.

T. +52-1-55-143893

M. +52-1-55-3232-9543

E. LA_Sales@miniprinter.com

