

sewoo

Desktop Label Printer

# LK-B30II



- Fast Print Speed : 152mm/sec
- Excellent Compatibility
- Easy to use and maintenance
- Support label design software "Label Cooker"
- Compact design and advanced performance



WiFi



Bluetooth



Barcode



Durable



Easy  
Loading



Fast  
Speed



Compact  
Design



Easy  
Replacement



## APPLICATION



## SPECIFICATIONS



### PRINTER CHARACTERISTICS

**Print Method**  
Direct thermal

**Print Speed**  
152mm/sec

**Print Width**  
104mm (4.1")

**Resolution**  
203 dpi (8dots/mm)

**Memory**  
Main Flash 1MB  
SDRAM 16MB  
FONT Flash 8MB

**Sensor**  
Gap, Black mark, Cover open

**Power**  
Type : External SMPS  
AC : 100~240Vac, 1.5A, 50/60Hz  
DC : 24Vdc 1.75A



### PHYSICAL CHARACTERISTICS

**Dimension (W x D x H)**  
7.48" x 10" x 4.29"  
(190 x 254 x 169 mm)

**Weight (Kg)**  
2kg



### MEDIA CHARACTERISTICS

**Media Type**  
Roll, Fanfold, Blackmark,  
Continuous, Gap, Notch Sensor

**Media Width**  
22 ~ 114mm

**Media Roll Diameter**  
Up to 127mm (5")

**Media Core Diameter**  
25.4mm (1") or 38.1mm (1.5")

**Thickness**  
0.065~0.20mm



### OPERATING CHARACTERISTICS

**Operating Temperature**  
0 ~ 40°C

**Operating Humidity**  
10 ~ 90%

**Storage Temperature**  
-20 ~ 60°C

**Storage Humidity**  
10 ~ 90%



### BARCODES

**1D**  
Code39, Code128 with subsets  
A/B/C/Auto, UCC/EAN-128, Code93,  
Codabar, Interleaved 2 of 5, UPC-A,  
UPC-E, UPC-A and E with 2 or 5 digit  
extension, EAN-8, EAN-13, EAN-8 and  
13 with 2 or 5 digit extensions,  
Postnet, Plessey, MSI-3, German Post  
CodeLogmars, Code11,  
UPC\_Interleaved 2 of 5, Industrial  
2 of 5, Standard 2 of 5, Planet, ANSI,  
Logmars

**2D**  
MaxiCode, PDF 417, Data Matrix,  
QR Code, MicroPDF417, AZTEC,  
Code 49, CODABLOCK, RSS



### SOFTWARE

**Emulations**  
EPL II, ZPL II Command compatible

**Drivers**  
Windows Driver  
Linux Driver  
Mac Driver

**SDKs**  
Windows SDK  
Android SDK  
iOS SDK



### INTERFACES

**Standard**  
USB, Serial(RS-232C), Ethernet

**Optional**  
Wi-Fi(802.11a/b/g/n),  
Bluetooth Smart Ready  
(Bluetooth5.2+BLE)



### CERTIFICATIONS

KCC, CE, CB, UL



### FONTS / GRAPHICS

**EPL II**  
6 bitmapped  
8x12, 10x16, 12x20, 14x24, 32x48,  
24x24(KSC5601)

**ZPL II**  
9 bitmapped  
5×9, 7×11, 10×18, 10x18, 15×28,  
13×26, 40×60, 13x21, 24x24  
2 smooth scalable(English, Korean)



### ACCESSORIES

**Standard**  
Power Cord, Power Supply,  
Interface Cable(USB)

**Optional**  
External Paper Supply

# sewoo

Republic of Korea [Head Office / R&D Center]  
28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea  
T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.  
Torrance, CA 90502, USA  
T. +1-310-617-7401  
E. NA\_sales@miniprnter.com

México Office  
Cuahtémoc, D.F. Mexico. CP 06500  
T. +52-1-55-3232-9543 M. +52-1-55-143893  
E. LA\_sales@miniprnter.com

