

sewoo

Advanced Desktop Label Printer

LK-B30IIE



- Excellent Compatibility with industry standards
- Ultra Compact and Durable
- Easy to use and maintain
- Optional Auto cutter, Peeler, Wireless Interface (Wi-Fi, Bluetooth)
- Supports label design software "Label Cooker"
- Versatile Font Types & Barcodes Printing Supported



WiFi



Bluetooth



Barcode



Durable



Easy Loading



Fast Speed



Compact Design



Easy Replacement



 BarTender™

BarTender UltraLite Available

APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method

Direct thermal

Print Speed

152mm/sec

Print Width

108mm (4.25")

Resolution

203 DPI (8 dots/mm)

Memory

Main Flash 1MB

SDRAM 16MB

FONT Flash 8MB

Sensor

Gap, Black mark, Cover open

Power

Type : External SMPS

AC : 100~240Vac, 2.0A, 50~60Hz

DC : 24Vdc 2.5A

Auto-Cutter (Optional)

Type : Guillotine

Life : 500,000 cuts,

Max 20 cycle/1min(0.06mm Paper)



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)

7.48" x 10.31" x 6.61"

(190 x 262 x 168 mm)

Weight (Kg)

1.52kg



MEDIA CHARACTERISTICS

Media Type

Roll, Fanfold, Blackmark,

Continuous, Gap, Punched hole,

Notch Sensor

Media Width

25.4~115mm

Media Roll Diameter

Up to 127mm (5")

Media Core Diameter

25.4mm (1")

Thickness

0.060~0.20mm



OPERATING CHARACTERISTICS

Operating Temperatures

5 ~ 40°C

Operating Humidity

25 ~ 85%

Storage Temperature

-20 ~ 60°C

Storage Humidity

10 ~ 90%



BARCODES

1D

Code39, Code128 with subsets

A/B/C/Auto, UCC/EAN-128, Code93,

Codabar, Interleaved 2 of 5, UPC-A,

UPC-E, UPC-A and E with 2 or 5 digit

extension, EAN-8, EAN-13, EAN-8 and

13 with 2 or 5 digit extensions,

Postnet, Plessey, MSI-3, German Post

CodeLogmars, Code11,

UPC_Interleaved 2 of 5, Industrial

2 of 5, Standard 2 of 5, Planet, ANSI,

Logmars

2D

MaxiCode, PDF 417, Data Matrix,

QR Code, MicroPDF417, AZTEC,

Code 49, CODABLOCK, RSS



SOFTWARE

Emulations

EPL II, ZPL II Command compatible

Drivers

Windows Driver

Linux Driver

Mac Driver

SDKs

Windows SDK

Android SDK

iOS SDK



FONTS / GRAPHICS

EPL II

6 bitmapped

8x12, 10x16, 12x20, 14x24, 32x48,

24x24(KSC5601)

ZPL II

9 bitmapped

5x9, 7x11, 10x18, 10x18, 15x28,

13x26, 40x60, 13x21, 24x24

2 smooth scalable(English, Korean)



INTERFACES

Standard

USB, Serial(RS-232C), Ethernet

Optional

Wi-Fi(802.11a/b/g/n),

Bluetooth Smart Ready Bluetooth5.2+BLE)



CERTIFICATIONS

CE, FCC, KC, UL, CB



ACCESSORIES

Standard

Power Cord, Power Supply,

Interface Cable(USB, Serial)

Optional

Auto cutter, Peeler

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.

475 North Martingale Rd., Suite 710
Schaumburg, IL 60173, USA

T. +1-859-992-5936

+1-312-550-9576

E. NA_Sales@miniprnter.com

México

IZA Business Center Torre Diana
Calle Rio Lerma No. 232, Piso 23, Oficina 2347
Col. Cuauhtemoc, C.P. 06500, Ciudad de México, México

T. +52-55-88527880 M. +52-55-143893

E. LA_Sales@miniprnter.com

