

sewoo

Board on the economic class being served with a great performance.

# LK-P25II



- Economic but, excellent performance
- Ultra Compact and Lightweight
- Large Battery Capacity
- Wide Compatibility
- USB-C Type Charging Port
- S-MDM (Sewoo MDM) supported



Bluetooth



Barcode



Portable




Durable



Drop Resistant



Easy Loading



Compact Design



Easy Maintenance



Improved Battery Life



S-MDM Support



## APPLICATION



## SPECIFICATIONS

### PRINTER CHARACTERISTICS

**Print Method**  
Direct thermal

**Print Speed**  
Up to 3.1ips (80mm/sec)

**Print Width**  
Up to 1.8" (48mm)

**Resolution**  
203 dpi (8dots/mm)

**Memory**  
8MB(Max 64MB),SRAM 8MB

**Battery Voltage / Capacity**  
3.6V 3250mAh Li-ion

4Hrs Charging time(Charger)  
6 Hrs Charging time(USB)

**Standby Time**  
63 Hrs

**Sensor**  
Paper end, Cover open,  
Black mark

**Reliability**  
TPH life : 50km

### PHYSICAL CHARACTERISTICS

**Dimension (W x D x H)**  
3.1" × 1.74" × 4.06"  
(79 × 44.4 × 103.2mm)

**Weight**  
190g

### INTERFACES

**Standard**  
USB C Type, Bluetooth Smart Ready  
(Bluetooth4.2+BLE), NFC Tag

### CERTIFICATIONS

KC, CE, FCC, IC, UL/cUL, Mfi,  
UKCA,BCS

### OPERATING CHARACTERISTICS

**Operating Temperature**  
14 ~ 122°F(-10 ~ 50°C)

**Operating Humidity**  
10 ~ 80%

**Storage Temperature**  
-4 ~ 140°F(-20 ~ 60°C)

**Storage Humidity**  
10 ~ 90%

**Drop Rating**  
5ft/1.5m (set only) to concrete  
6ft/1.8m with case to concrete

**Dust-and Water-resistance Rating**  
IP42 (With Case - TBD)

### BARCODES

**1D**  
EAN-8, EAN-8(+2+5), EAN-13,  
EAN-13(+2+5), Codabar, Code11,  
Code39, Code93, Code128, ITF,  
LUPC-A(+2+5), UPC-E, UPC-E(+2+5),  
Planet, UPC-A etc

**2D**  
QR, PDF417, MicroPDF417, Maxicode,  
Datamatrix, Aztec, RSS14, TLC39

### SOFTWARE

**Emulations**  
ESC/POS, CPCL, ZPL  
Command compatible

**Drivers**  
Windows Driver(XP ~, Server2003 ~),  
Window CE & Mobile Driver & SDK  
(CE 4.2~, Mobile 5.0~), Linux Driver,  
Mac Driver, OPOS Driver,  
JavaPOS Driver, iOS SDK,  
Android(6.0 ~) SDK

### MEDIA CHARACTERISTICS

**Media Type**  
Thermal paper

**Media Width**  
2.2" (58mm)

**Media Core Diameter**  
0.4" (12.5mm ± 0.5mm)

**Media Roll Diameter**  
1.5" (40mm)

**Thickness**  
0.06mm

### FONTS / GRAPHICS

**Character Type**  
FontA(12x24), FontB(9x17), Asian Font  
(KOR, JPN, CHN\_GB2312, CHN\_BIG5),  
Font0/1/2/4/5/6/7, Resident TTF,  
Downloadable TTF, FontA~H, FontGS,  
Resident TTF(Font0), Font1~8

**Characters per Line (CPL)**  
Font A(12x24): 32cpl,  
Font B(9x17): 42cpl,

**Character Set**  
95 Alphanumeric,  
14 International,  
128 x 18 Graphic

### ACCESSORIES

**Standard**  
Thermal Roll Paper,  
Belt Clip & Battery Cover  
AC/DC Adaptor 5VDC

**Optional**  
Carrying Case (with Belt Clip),  
Shoulder Strap, IP54 Case

# sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea  
T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

#### USA, Inc.

Torrance, CA 90502, USA  
T. +1-310-617-7401  
E. NA\_sales@miniprnter.com

#### México Office

Cuauhtémoc, D.F. Mexico. CP 06500  
T. +52-1-55-3232-9543 M. +52-1-55-143893  
E. LA\_sales@miniprnter.com

#### China Office

Shang hai shi, Song jiang qu  
T. +86-177-1729-9100  
E. sales@miniprnter.com

