

sewoo

Super-rugged & high-portability with LCD display

LK-P43II



- Fast Print Speed
- Excellent Compatibility
- Quick and easy to support peel mode
- Durable and resistant to water and dust
- S-MDM (SSM & SCM)
- Accessories : Shoulder Strap, Car Charger



Non Peeler
NON PEELER

Peeler
PEELER



WiFi



Bluetooth



Barcode



Portable



Durable



Rugged Design



Drop Resistant



Easy Loading



100
mm/sec

Fast Speed



Compact Design



Easy Maintenance



Improved Battery Life



S-MDM Support

APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method

Direct thermal

Print Speed

100mm/sec

Print Width

104mm, 832 Dots/line

Resolution

203 dpi (8dots/mm, 0.125 Pitch)

Memory

FLASH : 16MB (Max.32MB)

SDRAM : 16MB(Max.32MB)

Battery Voltage / Capacity

7.2V 3350mAh, 6700mAh

3.5Hrs Charging time(3350mAh)

6.5Hrs Charging time(6700mAh)

118Hrs Stand-by(6700mAh)

Sensor

Paper end, Gap, Black mark,

Cover open, Peeler detect,

Peeler S/W

Reliability

TPH life : 50km



PHYSICAL CHARACTERISTICS

Dimension (W x L x D)

6.5"×6.8"×3.1"

(166 × 174 × 80mm)

Weight

1kg (with 2600mAh battery)

Display

WQVGA Color graphic 3" TFT LCD



INTERFACES

Standard

USB, Serial(RS-232C)

Optional

Wi-Fi(802.11a/b/g/n),

Bluetooth Smart Ready

(Bluetooth5.2+BLE)



ACCESSORIES

Standard

AC Cord, USB Cable, Serial Cable,

Battery Pack, Thermal Roll Paper,

Belt Clip, Power Adaptor

Optional

Shoulder Strap, Vehicle Charger,

Battery Cradle (P43), Peeler, RTC



OPERATING CHARACTERISTICS

Operating Temperature

-21 ~ 55°C

Operating Humidity

10 ~ 90%

Storage Temperature

-30 ~ 65°C

Storage Humidity

10 ~ 90%

Dust-and Water-resistance Rating

IP54 certified

Drop Rating

1.8m(set only)



BARCODES

1D

EAN-8, EAN-8(+2+5), EAN-13,

EAN-13(+2+5), Codabar, Code11,

Code39, Code93, Code128, ITF,

UPC-A(+2+5), UPC-E, UPC-E(+2+5),

Planet, etc

2D

QR, PDF417, MicroPDF417, Maxicode,

Datamatrix, Aztec, RSS14, TLC39



SOFTWARE

Emulations

ESC/POS, CPCL, ZPL Command

compatible

Drivers

Windows Driver(XP ~, Server2003 ~),

Window CE & Mobile Driver & SDK

(CE 4.2~, Mobile 5.0~), Linux Driver,

Mac Driver, OPOS Driver, JavaPOS

Driver, iOS SDK, Android(6.0 ~) SDK



MEDIA CHARACTERISTICS

Media Type

Thermal Receipt/Label

Media Width

50~112mm

Media Core Diameter

12.5mm ± 0.5mm

Media Roll Diameter

Max. Ø 56mm

Thickness

0.06 ~ 0.16mm



FONTS / GRAPHICS

Character Type

FontA(12x24), FontB(9x17),

Font0/1/2/4/5/6/7, TTF Font0, FontA~H,

FontGS, Font1~8, Asian Font(KOR, JPN,

CHN_GB2312, CHN_BIG5), Resident TTF,

Downloadable TTF, Downloadable Bitmap

Characters per Line (CPL)

Font A(12x24): 69 columns

Font B(9x17): 92 columns

Character Set

Alpha numeric character : 95

Expanded graphic :

128*18 page(1 space page)

International character : 14



CERTIFICATIONS

KC, CE, FCC, IC, UL/cUL, MFI,

UKCA, BCS, CB

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA

T. +1-310-617-7401

E. NA_sales@miniprnter.com

México Office

Cuauhtémoc, D.F. Mexico. CP 06500

T. +52-1-55-3232-9543 M. +52-1-55-143893

E. LA_sales@miniprnter.com

China Office

Shang hai shi, Song jiang qu

T. +86-177-1729-9100

E. sales@miniprnter.com

