

sewoo

Robust and durable label mobile printers

# LK-P30II



- Fast Print Speed
- Excellent Compatibility
- Quick and easy to support peel mode
- Rugged design for Drop resistant
- Durable and resistant to water and dust
- S-MDM (SSM & SCM)
- Accessories : Shoulder Strap, Car Charger



WiFi



Bluetooth



Barcode



Portable



Durable



Rugged Design




Drop Resistant



Easy Loading



Fast Speed



Compact Design



Easy Maintenance



Improved Battery Life



S-MDM Support

## APPLICATION



## SPECIFICATIONS



### PRINTER CHARACTERISTICS

**Print Method**  
Direct thermal

**Print Speed**  
100mm/sec

**Print Width**  
72mm, 576 Dots/line

**Resolution**  
203 dpi (8dots/mm, 0.125 Pitch)

**Memory**  
16MB(Max.32MB) Flash,  
8MB SDRAM

**Battery Voltage / Capacity**  
7.4V 2600mAh Li-ion,  
7.2V 3350mAh Li-ion

**Battery Charge Time**  
3.3Hrs (2600mAh),  
4Hrs (3350mAh)

**Standby Time**  
100Hrs (2600mAh),  
90Hrs (3350mAh)

**Sensor**  
Paper end, Black mark,  
Cover open, Gap

**Reliability**  
TPH life : 50km



### PHYSICAL CHARACTERISTICS

**Dimension (W x L x D)**  
4.72" × 5.98" × 2.75"  
(120 × 152 × 70mm)

**Weight**  
640g (with Battery)



### INTERFACES

**Standard**  
USB, Serial(RS-232C)

**Option**  
Wi-Fi(802.11a/b/g/n),  
Bluetooth Smart Ready  
(Bluetooth5.2+BLE)



### CERTIFICATIONS

KC, CE, FCC, IC, UL/cUL, Mfi,  
UKCA, BCS, CB



### OPERATING CHARACTERISTICS

**Operating Temperature**  
-10 ~ 50°C

**Operating Humidity**  
10 ~ 80%

**Storage Temperature**  
-20 ~ 60°C

**Storage Humidity**  
10 ~ 90%

**Dust-and Water-resistance Rating**  
IP42, IP54(with case) certified

**Drop Rating**  
1.2m(set only), 1.8m(with case)



### BARCODES

**1D**  
EAN-8, EAN-8(+2+5), EAN-13,  
EAN-13(+2+5), Codabar, Code11,  
Code39, Code93, Code128, ITF,  
UPC-A(+2+5), UPC-E, UPC-E(+2+5),  
Planet, etc

**2D**  
QR, PDF417, MicroPDF417, Maxicode,  
Datamatrix, Aztec, RSS14, TLC39



### SOFTWARE

**Emulations**  
ESC/POS, CPCL, ZPL

**Drivers**  
Windows Driver(XP ~, Server2003 ~),  
Window CE & Mobile Driver & SDK  
(CE 4.2~, Mobile 5.0~), Linux Driver,  
Mac Driver, OPOS Driver, JavaPOS  
Driver, iOS SDK, Android(6.0 ~) SDK



### MEDIA CHARACTERISTICS

**Media Type**  
Thermal Receipt/Label

**Media Width**  
25 ~ 80mm

**Media Core Diameter**  
12.5mm ± 0.5mm

**Media Roll Diameter**  
Max. Ø 56mm

**Thickness**  
0.06 ~ 0.16mm



### FONTS / GRAPHICS

**Character Type**  
FontA(12x24), FontB(9x17),  
Font0/1/2/4/5/6/7, TTF Font0, FontA~H,  
FontGS, Font1~8, Asian Font(KOR, JPN,  
CHN\_GB2312, CHN\_BIG5), Resident TTF,  
Downloadable TTF, Downloadable Bitmap

**Characters per Line (CPL)**  
Font A(12x24): 48 columns,  
Font B(9x17): 64 columns

**Character Set**  
Alpha numeric character : 95  
Expanded graphic :  
128\*18 page(1 space page)  
International character : 14



### ACCESSORIES

**Standard**  
USB Cable, Battery Pack, Serial Cable  
Thermal Roll Paper, Belt Buckle,  
Battery Charger (8.4V)

**Optional**  
Battery Cradle (P30), Vehicle Charger,  
Leather Case, Shoulder Trap, RTC  
4 Bay Cradle

# sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea  
T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprinter.com

www.miniprinter.com

#### USA, Inc.

Torrance, CA 90502, USA  
T. +1-310-617-7401  
E. NA\_sales@miniprinter.com

#### México Office

Cuauhtémoc, D.F. Mexico. CP 06500  
T. +52-1-55-3232-9543 M. +52-1-55-143893  
E. LA\_sales@miniprinter.com

#### China Office

Shang hai shi, Song jiang qu  
T. +86-177-1729-9100  
E. sales@miniprinter.com

