

sewoo

Ultra Compact Mobile Printer

LK-P22



- Fast Print Speed : 100mm/sec
- Ultra Compact and Lightweight
- Excellent Compatibility
- NFC for easy Bluetooth pairing
- Durable and resistant to water and dust
- S-MDM (SSM & SCM)
- Accessories : Belt Clip, Belt Bracket & Strap, Car Charger



WiFi



Bluetooth



Barcode



Portable



Durable



NFC



Drop Resistant



Easy Loading



Fast Speed



Compact Design



Easy Maintenance



Improved Battery Life



S-MDM Support

APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method
Direct thermal

Print Speed
100m/sec

Print Width
48mm, 384dots/line

Resolution
203 DPI

Memory
8MB(Max 64MB)
SDRAM 8MB

Battery Voltage / Capacity
7.4V 1450mAh Li-ion
1.7 Hrs Charging time
36 Hrs Stand-by

Sensor
Paper end, Cover open

Reliability
TPH life : 50km



PHYSICAL CHARACTERISTICS

Dimension (W x L x D)
3.14" × 4.70" × 1.73"
(80×119.4×44mm)

Weight
242.5g(With Battery)



INTERFACES

Standard
USB

Optional
Wi-Fi(802.11a/b/g/n), Bluetooth
Smart Ready(Bluetooth5.2+BLE)



CERTIFICATIONS

KC, CE, FCC, IC, UL/cUL, M, UKCA,
BCS, CB



OPERATING CHARACTERISTICS

Operating Temperature
-10 ~ 50°C

Operating Humidity
10 ~ 80%

Storage Temperature
-20 ~ 60°C

Storage Humidity
10 ~ 90%

Dust-and Water-resistance Rating
IP42 certified

Drop Rating
1.5m(set only), 1.8m(with case)



BARCODES

1D
EAN-8, EAN-8(+2+5), EAN-13,
EAN-13(+2+5), Codabar, Code11,
Code39, Code93, Code128, ITF,
UPC-A(+2+5), UPC-E, UPC-E(+2+5),
Planet, etc

2D
QR, PDF417, MicroPDF417, Maxicode,
Datamatrix, Aztec, RSS14, TLC39



SOFTWARE

Emulations
ESC/POS, CPCL, ZPL Command
compatible

Drivers
Windows Driver(XP ~, Server2003 ~),
Window CE & Mobile Driver & SDK
(CE 4.2~, Mobile 5.0~), Linux Driver,
Mac Driver, OPOS Driver, JavaPOS
Driver, iOS SDK, Android(6.0 ~) SDK



MEDIA CHARACTERISTICS

Media Type
Thermal Receipt

Media Width
58mm

Media Core Diameter
12.5mm ± 0.5mm

Media Roll Diameter
Max. Ø 40mm

Thickness
0.06mm



FONTS / GRAPHICS

Character Type
FontA(12x24), FontB(9x17),
Font0/1/2/4/5/6/7, TTF Font0,
FontA~H, FontGS, Font1~8,
Asian Font(KOR, JPN, CHN_GB2312,
CHN_BIG5), Resident TTF, Downloadable
TTF, Downloadable Bitmap

Characters per Line (CPL)
Font A(12x24): 32 columns
Font B(9x17): 42columns

Character Set
Alpha numeric character : 95
Expanded graphic : 128*18 page(1 space page)
International character : 14



ACCESSORIES

Standard
USB Cable, Battery Charger(8.4V)
Battery Pack, Thermal Roll Paper,
Belt Clip

Optional
Set cradle, Battery cradle,
Leather case + Shoulder Strap

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea
T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA
T. +1-310-617-7401
E. NA_sales@miniprnter.com

México Office

Cuauhtémoc, D.F. Mexico. CP 06500
T. +52-1-55-3232-9543 M. +52-1-55-143893
E. LA_sales@miniprnter.com

China Office

Shang hai shi, Song jiang qu
T. +86-177-1729-9100
E. sales@miniprnter.com

